




CR173135 



CR173135 43W also available 25W and 30W

Input Voltage AC220-240V, Multivoltage
Light Power 43W also available 25W and 30W
Luminous flux ~4180lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option


CR330135 



CR330135 2*43W also available in 25W and 30W

Input Voltage AC220-240V, Multivoltage
Light Power 2*43W also available in 25W and 30W
Luminous flux ~8020lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option

CR487135 




CR487135 3*43W also available 25W and 30W

Input Voltage AC220-240V, Multivoltage
Light Power 3*43W also available 25W and 30W
Luminous flux ~11480lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option

CR168135 

CR168135 TRIM-LESS also available 25W and 30W



Input Voltage AC220-240V, Multivoltage
Light Power 1*43W also available
Luminous flux ~4170lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



CR325135 

CR325135 TRIM-LESS also available 25W and 30W

Input Voltage AC220-240V, Multivoltage
Light Power 2*43W also available 25W and 30W
Luminous flux ~8020lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option



CR482135 

CR482135 TRIM-LESS also available 25W and 30W

Input Voltage AC220-240V, Multivoltage
Light Power 3*43W also available 25W and 30W
Luminous flux ~11480lm
Light Source CREE, other options available
CCT 2700K, 3000K, 4000K
CRI 80 as standard, CRI90, 95, 97
Beam Angle Reflector 15°, 24°, 38°
Driver, Khun, Xz other options available
Dimmable 0-10V, Triac, Dali as an option

